

SHAZAND Petrochemical Company

## POLY PROPYLENE

### Moplen HP500M (Injection Moulding)

Typical properties	Test method (ASTM)	Unit	Value
MFR @230°C, 2.16 kg	D1238/L	gr/10min	9
Flexural Modulus	D790	Mpa	1550
Notched Izod Impact@23°C	D256	J/m	37
Tensile Strength@Yield	D638	Mpa	35
Elongation@Yield	D638	%	12
Vicat Softening Point, 10N	D1525	°C	154
HDT(0.46N/mm <sup>2</sup> )	D648	°C	95
Rockwell Hardness	D785	R.Scale	102
Oven Aging@150°C	D3012	Hours	360

➤ Values shown are averages & are not to be considered as product specifications.

#### ❖ Main application & Characteristics:

**Moplen HP500M** is a polypropylene homo-polymer for injection moulding. Because of its good flow properties, this grade offers easy processing. Articles produced from **Moplen HP500M** exhibit high stiffness.

**Moplen HP500M** is widely used for injection moulding consumer goods such as food containers, house wares, toys & garden furniture.

Other major applications are components for appliances & parts for the automotive industry.

\* **Moplen HP500M** is suitable for food contact.

 +77017111544  
 +96893915661

 Email: [info@atlaspetro.com](mailto:info@atlaspetro.com)

 [www.atlaspetro.com](http://www.atlaspetro.com)