

SHAZAND Petrochemical Company

POLY PROPYLENE

Moplen HP500N (Fibre)

Typical properties	Test method (ASTM)	Unit	Value
MFR @230°C, 2.16 kg	D1238/L	gr/10min	12
Felexural Modulus	D790	Mpa	1400
Notched Izod Impact@23°C	D256	J/m	20
Tensile Strength@Yield	D638	Mpa	34
Elongation@Yield	D638	%	12
Vicat Softening Point,10N	D1525	°C	154
HDT(0.46N/mm ²)	D648	°C	95
Rockwell Hardness	D785	R.Scale	102
Oven Aging@150°C	D3012	Hours	360

➤ Values shown are averages & are not to be considered as product specifications.

❖ Main application & Characteristics:

Moplen HP500N is a medium-high fluidity polypropylene homo-polymer. Moplen HP500N is particularly suitable for the production of heavy denier staple fibre & continuous filament. Moplen HP500N exhibits good process stability & constant, high flow during extrusion.

Moplen HP500N is developed for the extrusion of staple fibres for spinning wool system fibres for carpets, rugs & garments such as overalls & socks.

Moplen HP500N is also suited for the production of continuous filament for ropes, belts & straps. Another typical application of Moplen HP500N is the extrusion of decorative ribbons.

* Moplen HP500N is suitable for food contact.

+77017111544
+96893915661

Email: info@atlaspetro.com

www.atlaspetro.com