

URMIA Petrochemical Company

## CRYSTAL MELAMINE

parameter	unit	
<b>Grade</b>		<b>Superior</b>
<b>PURITY</b>	<b>% ( w/w )</b>	<b>&gt; 99.8</b>
<b>HUMIDITY</b>	<b>% ( w/w )</b>	<b>&lt; 0.1</b>
<b>PH</b>		<b>7.5 - 9.5</b>
<b>SOLUBILITY in HCHO</b>	<b>Minute</b>	<b>Max 10</b>
<b>COLOUR</b>	<b>HAZEN (Pt - Co )</b>	<b>&lt; 20</b>
<b>TURBIDITY</b>	<b>NTU</b>	<b>&lt; 20</b>
<b>SIZE (below 80 mesh)</b>	<b>Mesh</b>	<b>min 80%</b>
<b>SOLUBILITY in H2O</b>	<b>-</b>	<b>20 C Clear</b>
<b>ASH</b>	<b>% ( w/w )</b>	<b>&lt; 0.03</b>
<b>Hydro fobe</b>	<b>Minute</b>	<b>30~70</b>



+77017111544  
+96893915661



Email: [info@atlaspetro.com](mailto:info@atlaspetro.com)



[www.atlaspetro.com](http://www.atlaspetro.com)